

Fixed angle notcher



The fixed angle notching machines are equipped with:

- Hydraulic functioning through two cylinders to grant a constant and smooth notching,
- A wide and rigid worktable with aluminium rods with directional triple functions, for the measuring the different type of notches,
- Angle squares guides equipped with nr. 3 reference holes without scales.
- Head configuration which allows the cuts longer than the blade length.
- Economic square rods,
- Cutting zone protection sheet made in Polycarbonate which allows a wide sight of the working area and maximum safety,
- Swarf collecting box..

FIXED ANGLE NOTCHING MACHINE	U.M.	FA 200/4	FA 200/6
Blade lenght	mm	205	205
Maximum thickness of the sheet	mm	4	6
Maximum thickness on stainless steel	mm	3	4
Holddown	-	0	2
Blade gap automatic regulation	-	Optional	Optional
Engine	Kw	2.2	2.2
Strokes per minute	N	45	45
Table dimension	mm	625x954	625x954
Height of working	mm	930	930
Hydraulic oil	Viscosity	46	46
Oil tank capacity (Oil not included)	Lt	25	25
Cutting angle	°	90	90
Stroke electronic control	-	Optional	Optional
Overall dimensions	mm	1000x1000x1100	920x970x1000
Approximate weight	Kg	370	390

